LIKIU

Likiu Unmanned Ground Vehicles



Civilian unmanned ground robots for inspection, logistics support and equipment integration. Chassis, control, payload, sensors and project-specific options are subject to confirmation.

Company: Zhongke Likiu (Jinan) Robot Co., Ltd.
Store: Independent Likiu storefront on x2xhub.com
Business contact: Hui Zhou, trade and sourcing contact.
Tel / WhatsApp: +86 186 2740 7019
Email: sardenesy@fixr2026.com
Telegram: @sardenesy | WeChat: 18627407019

Source: user-supplied Likiu Drone Manual and 产品目录Catalog.pdf. This is a clean derivative limited to the products in this booth. Specifications are not an offer, warranty or certification. Confirm model, configuration and compliance before purchase.

Likiu X1 All-Terrain Quadruped Robot



All-terrain quadruped robot for inspection, logistics support and industrial equipment integration.

- **Dimensions:** 930 × 543 × 622 mm
- **Weight:** 35–40 kg
- **Degrees of freedom:** 12
- **Maximum obstacle-climbing height:** 50 cm
- **No-load endurance:** 5 h
- **Loaded endurance:** 3 h at 20 kg load
- **Continuous operating load:** 25 kg
- **Maximum standing load:** 120 kg
- **High-precision LiDAR:** 2 units
- **Protection rating:** IP67
- **Operating temperature:** -20 °C to 55 °C
- **Source:** Likiu Drone Manual, PDF page 35

Likiu T4 Four-Wheeled Unmanned Ground Vehicle



Four-wheeled unmanned ground platform for industrial transport, inspection and equipment integration.

- **Dimensions:** 1100 × 800 × 400 mm
- **Load capacity:** 100 kg
- **Speed:** 0–15 km/h
- **Motor:** 48 V DC brushless geared motors, 600 W × 4
- **Tire:** 370 mm diameter × 150 mm width
- **Remote-control range:** 0–200 m; optional 0–2000 m
- **Source:** Likiu Drone Manual, PDF page 37

Likiu T6 Six-Wheeled Unmanned Ground Vehicle



Six-wheeled unmanned platform for industrial payloads and remote-controlled field operations.

- **Dimensions:** 1120 × 800 × 400 mm
- **Load capacity:** 100 kg
- **Speed:** 0–5 km/h
- **Motor:** 24 V DC brushed 250 W or optional 24 V DC brushless 300 W × 6
- **Tire:** 300 mm diameter × 150 mm width
- **Remote-control range:** 0–200 m; optional 0–2000 m
- **Source:** Likiu Drone Manual, PDF page 37

Likiu T8 Eight-Wheeled Unmanned Ground Vehicle



Heavy unmanned ground platform with eight wheels, bridge suspension and dual-drive control.

- **Dimensions:** 1700 × 1100 × 450 mm
- **Load capacity:** 300 kg
- **Speed:** 0–7 km/h
- **Motor:** 48 V DC brushless permanent-magnet synchronous motors, 1000 W × 4
- **Suspension:** Bridge-type suspension
- **Controller:** Intelligent dual-drive controller
- **Source:** Likiu Drone Manual, PDF page 37

Likiu D80 Tracked Unmanned Ground Vehicle



Tracked unmanned ground platform for industrial transport and field equipment integration.

- **Dimensions:** 1000 × 800 × 400 mm
- **Load capacity:** 200 kg
- **Speed:** 0–5 km/h
- **Motor:** 48 V DC brushless permanent-magnet synchronous motors, 1000 W × 2
- **Track:** High-speed track, 150 mm width
- **Remote-control range:** 0–200 m; optional 0–2000 m
- **Source:** Likiu Drone Manual, PDF page 37

Likiu D50 Compact Tracked Unmanned Ground Vehicle



Compact tracked unmanned platform for light logistics, inspection and equipment-carrier applications.

- **Dimensions:** 700 × 500 × 300 mm
- **Load capacity:** 30 kg
- **Speed:** 0–4 km/h
- **Motor:** 48 V DC brushless permanent-magnet synchronous motors, 500 W × 2
- **Track:** High-speed track, 100 mm width
- **Remote-control range:** 0–200 m; optional 0–2000 m
- **Source:** Likiu Drone Manual, PDF page 37

Likiu D100 Tracked Unmanned Ground Vehicle



Heavy tracked unmanned ground platform with a 300 kg load capacity for industrial logistics and integration.

- **Dimensions:** 1400 × 1000 × 450 mm
- **Load capacity:** 300 kg
- **Speed:** 0–7 km/h
- **Motor:** 48 V DC brushless permanent-magnet synchronous motors, 1500 W × 2
- **Track:** High-speed track, 150 mm width
- **Remote-control range:** 0–200 m; optional 0–2000 m
- **Source:** Likiu Drone Manual, PDF page 37